

Infrared and 433MHz RF control

Graphical interface is completely customizable

2.4" Color LCD touchscreen display

Tilt-activated backlit buttons

Convenient, intuitive selection of buttons

All hard buttons are fully programmable



Style and simplicity.

The essence of style and simplicity, the Pro24.r extends your reach without straining your budget. The customizable LCD touchscreen display and programmable hard buttons assure intuitive control.

Advanced wizard-based software keeps programming extremely efficient for professional integrators while offering advanced control and unmatched customization.

Rock solid reliability

When paired with the ProLink.r control processor, the Pro24.r remote delivers fast and reliable 433 MHz one-way RF communication.

The ProLink.r processor features an Ethernet port for network control of devices, four IR ports, two voltage-sensing inputs, and one-way (LAN) support for the ProPanel App on Apple iPad® and iPhone®.



ProLink.r Control Processor



Pro.Dock Charging Dock

SPECIFICATIONS

Color touchscreen display	2.4" TFT LCD
RF control	1-way (433 MHz)
Compatible control processor	Pro Control ProLink.r
Control via infrared (IR)	Yes (Capable of IR learning)
Charging	Pro.Dock (Optional) or USB Cable
Rechargeable battery	Lithium Ion
Finish options	Gloss Finish
Number of commands and macros allowed	Unlimited (Limited only by available memory)
Number of controlled devices	Unlimited (Limited only by available memory)
Customizable graphics via programming software	Yes, Pro Control Studio
Dimensions H x W x D	9.79" x 2.23" x .9" (248.6mm x 56.6mm x 22.9mm)
Warranty	3 years (parts & labor)